

FastLane™ 7111

Series Secure Network Gateway

Multiservice Network Connectivity, Security, & VPN appliances

Connecting People, Places, & Things™

- 1 Robust Access Router & Endpoint
- 2 BEST Tunneling/VPN Connectivity
- 3 HIGHEST Redundancy
- 4 HIGHEST Security & Privacy
- 5 BEST Device Management

Model 7111 Series Highlights

- Full access router with Firewall
- Integrated 802.11 b/g/n Wi-Fi
- Dual-Radio 802.11 ac option
- External bulk Antenna Connectors
- Sturdy all metal enclosure
- Integrated wall mount flanges
- 8 LED Status Indicators
- 5 Wired Ethernet ports

- Branch and SoHo Connectivity
- Networking Support for wired & wireless devices is required
- Perfect for networks for 250 users or less
- 802.11 b/g/n Wi-Fi connects all your devices to both the LAN and the Tunnel
- Can use the Wi-Fi as WAN uplink or access point simultaneously
- MPLS or Lease-line replacement with Active/Active redundancy
- Load-Balance and Link Aggregation supporting up to 64 independent network connections

The World's Longest Ethernet Cable™

The IpTL FastLane 7111 provides wired Fast-Ethernet and wireless 802.11 b/g/n, and optional AC connectivity with always-on secure VPN access to enterprise resources. Perfect for branch office connectivity & MPLS/leased-line circuit replacement, the 7100 Series provides wireless and wired connectivity, full routing, and full redundancy/high-availability in an integrated and fully managed package.

IpTL FastLane products are designed for access connectivity and includes all the expected networking features ensuring success to your project including routing/forwarding, VLANs, and stateful inspection firewall. For redundancy and failover applications, the M7100 Series can connect to multiple networks and provide active/active failover as well as link-bonding over multiple Internet services. Additionally, the cellular can use the wireless network in either hot or passive standby with automatic failover/failback. Redundancy is network transparent and does not require any reconfiguration of networking parameters or infrastructure.



Device Overview

- Sturdy all-metal enclosure; cool low-power & fan-less operation. 8 status LEDs: System, Ethernet, Tunnel, Firewall
- Provides a single Transparent Point-to-Point Ethernet tunnel bridged or L3 Routed links, full-duplex, and transparent operation.
- Auto-discovery of tunnel end-points through NAT/Routers/Proxy's.
- Unlimited host support — no network host limitation. Unlimited Networks.
- User configurable compulsory tunnels or split-tunnel operation.
- Firewall and ACL's provide granular traffic management as well as protection for both Local, Uplink, and each Tunnel.
- AutoConnect™, FastLaneNBX™ and FlexPath™ redundancy.
- Connect with any 4G, WiFi, or Wired IP connection including NAT and nested NAT environments.

Network Interface

- 5 ports 802.3TX Fast-Ethernet, RJ45 jacks; Auto-sensing all ports.
- 802.11 b/g/n WiFi Access Point and wireless client uplink with WPA/WPA2, and MAC deny/allow.
- 802.11 ac with dual-radio support (b/g/n + ac)
- Dual RP-SMA 2dBi detachable antennas. Selectable country codes.
- Any interface can be used to establish tunnel.

Management & Configuration

- Internal web server and control with selectable HTTP/HTTPS.
- SNMP v1 MIB II; User selectable enable/disable, SNMP Variables, Tunnel Status & Tunnel Octet In/Out, Ethernet Status & Ethernet Octet In/Out. SNMP Traps for device and tunnel events.
- Syslog output with configurable server.
- User Definable IP Address and Subnet Mask and Port for management.
- DHCP client for automatic address with simultaneous static secondary IP.
- Use with IpTL Model T7700 management server for independent positive control of endpoints via separate independent routed tunnel. Can run HTTP/SNMP/Syslog.
- GPS: Indoor reception better than -165 dBm with A-GPS; Accuracy 3m, TIF Cold start 42s, Multi Channel L1 1575.52Mhz. NEMA 0183 raw data output available.

Redundancy & High-Availability

- Active/Active Multipath Redundancy, WAN Link Auto failover with Multiple Internet Providers
- Active Deadpeer detection with Multisite uptime failover mechanism.
- No MAC Spoofing VRRP / HSRP Failover.
- Multi-interface Link Bonding & Load balancing- up to 64 links

Ordering Information

- 10070-7111-01** Secure Network Gateway with 5x Ethernet TX Ports and integrated 802.11 b/g/n Wi-Fi
- 10070-7121-01** Secure Network Gateway with 5x Ethernet TX Ports and integrated 802.11 ac + b/g/n Wi-Fi

Connectivity

- TLS, L2TPv3, PPTPWrapper Tunnel operations with AES-256 CBC key encryption (selectable DES-EDE3-CBC, 3DES-CBC, Blowfish-CBC). Perfect Forward Secrecy.
- Configurable TCP/UDP tunnel with single port for all control & payload. No-configuration NAT and Firewall traversal.
- Dynamic keying and automatic rekeying (default every 5 minutes) with X.509 PKI certificates. Username/Password option for tunnel authorization. Separate per-tunnel password for link authorization.
- Auto-learning with 8,192 MAC address table and unlimited hosts and networks support between LANs.
- Jumbo Ethernet frames with default MTU of 2K. VLAN (4,094) tagging on Client or Server; VLAN trunking out single Ethernet; InterVLAN routing. Will pass VLANs, VTP, & ISL.
- User selectable voluntary/compulsory and tunnel gateway modes through filters. Compulsory dictates all traffic will go through tunnel. No local-to-uplink access. Voluntary tunnel will only ARP for tunnel subnet traffic/hosts. Default Internet access via local router.
- ACL/Firewall permit/allow traffic from any interface. Separate Firewall rules for device access.
- Lossless compression—typical 20%-30% efficiency.
- Integrated DHCP client and server, DNS server, & NTP client.
- RealTimeResource™ DNS services & AutoConnect™ standard. Built in DynDNS client.
- Routed mode supports full IPv4 routing.
- IPSharing™ HalfBridge with Tunnel NAT Permits/Forwards.

Filtering & Quality of Service

- User configurable L2 and L3 filters on IP/Port or MAC Address. Statefull inspection processing and filtering with new, established, or related operation. Quick access buttons for immediate config.
- DSCP/TOS priority into three queues. E.g. EF = priority queue 0.

Operating

- Desktop operation mounting. Integral Wall mount holes flages.
- 12VDC@1A power input via coax barrel jack
- Operating Temperature: 0° to 50°C Humidity: up to 90% non-condensing

Regulatory Compliance & Certifications

- NRTL Safety: UL 60950-1, CSA C22.2 No. 60950-1; AS / NZS 3260, TS 001; Emissions: FCC Part 15 Class B/C, EN 55022A
- CE Mark, RoHS, WEEE,
- UAE TRA Auth: No. ER0091039/12; Oman TRA

To learn more, contact your IPTL Representative, Authorized Reseller, or Sales Agent or visit our Web site at www.IpTechnologyLabs.com

Specifications subject to change without notice. This document is for planning purposes only, and is not intended to create, modify or supplement any IPTL specifications or warranties relating to these products or services. Information and/or technical specifications supplied within this document do not waive (directly or indirectly) any rights or licenses – including but not limited to patents or other protective rights of IP Technology Labs, LLC. ©2016 IP Technology Labs, LLC All trademarks are the property of their registered owners. Rev: IPTL7111 Series v.3.02

IP Technology Labs
Network Communications Simplified™

3470 Olney-Laytonville Rd #313
Olney Maryland USA
T: +1 301 570 6611
F: +1 301 570 8049
W: <http://IpTechnologyLabs.com>
E: sales@IpTechnologyLabs.com